

MARTIN JOSE DEL CASTILLO S. FEBRUARY 25, 2019





Often imitated but never equaled.


It's no surprise the competition envies our original design. This agile and versatile personnel carrier has it all: A narrow deck, four wheels for greater stability on rough terrain, powerful motor, rugged automotive differential and larger self-adjusting drum brakes, high-strength tubular frame, all-steel body, bolt-on front bumper and side bar protection, easy-to-access under-seat battery compartment... The list keeps going. It can also pull up to 6,000 lbs., making it a great tow tractor.




Personnel Carriers, Tow Tractors Other Models : 24V









Dimensions

VEHICLE

Height	45"	1,143 mm
Length	77"	1,956 mm
Width	30"	762 mm
Wheel Base	n/a	n/a
Ground Clearance	n/a	n/a
DECK		
Height	25"	635 mm
Width	30"	762 mm
Length	20"	508 mm
UNIT WEIGHT		
With Batteries	n/a	n/a
Without Batteries	n/a	n/a
BATTERIES		
Height	n/a	n/a
Length	n/a	n/a
Width	n/a	n/a
Weight - Min	n/a	n/a
weight - white	11/d	11/4

Performances

١.	-		۰.	~		
v	-	п.			L	с

Passengers	1	
Load Capacity	500 lbs	227 kg
Tow Capacity	6,000 lbs	2,722 kg
Drawbar Pull - Normal	n/a	n/a
Drawbar Pull - Ultimate	n/a	n/a
Speed MPH	8 mph	13 km/h
Turning Radius	75"	1,905 mm

Vehicle shown may have optional accessories and is provided for illustrative purposes only.

Specifications and standard equipment are subject to change without notice.

Specifications

POWERTRAIN Motor 10 hp shunt motor Controller SEPEX Electronic speed controller Drive Axle Helical gear differential Brakes Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake, regenerative braking 4.8x8 LRB pneumatic tires Wheels Direct drive Transmission Dual coil springs and shock absorber on rear Suspension Starter n/a Clutch n/a Engine n/a ENERGY 36 Volt Voltage Battery Six 6V-225AH batteries Charger High-Frequency Charger, improves battery performance, prevents current surge, 50/ 60HZ, 110/220VAC Alternator n/a Fuel n/a CHASSIS Body 14-G diamond-plate steel body, tubular frame Color Security orange or federal yellow Lights LED headlight & tail/brake light

OPERATOR COMPARTMENT

Steering	Automotive Steering Wheel
Seats	Bucket seat on slide adjusters
Indicators	Battery status indicator
Safety	Reverse alarm, deadman seat switch, horn
Accessories	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.

Standards

Conforms to requirements for type E, UL 583, ANSI B56.9

Body Options	
240-052H36V	8" rear step with hitch plate
Cabs & Top Covers	
250-041	Steel cab and doors, wiper, rearview mirror
Driver Area Options	
360-020	Digital battery gauge with hour meter (included with AC package when applicable)
Hitches	
242-057	Rear bumper and clevis hitch with safety spring
Lights	
240-024K	Headlights on key switch
Safety Features	
360-023	Motion beeper
240-025	Pole mounted strobe light, amber
Seats	
250-051	Convertible backrest and bench seat (requires 8" or 12" rear footstep)
Wheels	
250-073	Solid softy rubber wheels

The list above shows the most popular options for this vehicle. More options are available. To learn more about the MP - 250 - 36V options, please contact your representative. Options, specifications and standard equipment are subject to change without notice. 

Martin Jose Del Castillo S. President

+52 662 210-7808 #104 mj.delcastillo@mmh.com.mx **Mex Material Handling** Los Mayos 13, Parque Industrial Hermosillo (Sonora) 83299

Mexico

www.motrec.com